

StorageLibrary™ T40+, T80+, T120+ and T160+

Professional, Scalable Tape Backup

The Tandberg Data StorageLibrary™ T40+, T80+, T120+ and T160+ tape libraries are professional backup and data protection solutions, providing maximum performance and scalable capacities up to 453TB*.

The Tandberg Data StorageLibrary T40+ Series incorporates the new Pass-Thru feature, allowing you to add additional drives and storage capacity as and when you need it. The Pass-Thru feature will allow up to three T40+ units to be stacked together in a 19" rack configuration.

The T40+ base unit is available with either 24 or 40 slots and the Capacity on Demand (COD) feature allows you to electronically upgrade the number of slots from 24 to 40. The number of slots can be increased further to 77, 114 or 151 slots by stacking additional T40+ units in Pass-Thru mode. Each T40+ unit can be installed with up to 4 half height LTO drives or up to 2 full height LTO drives and supports LVD SCSI, Native Fibre Channel or SAS connectivity.

The T40+ Series is designed to improve efficiency and minimize IT downtime. The Performance on Demand (POD) feature allows you add drives or upgrade to the next LTO generation, increasing your library's performance and capacity. The Web browser-based remote management interface allows you to monitor, control, configure and diagnose problems from anywhere in the world. The T40+ Series supports system monitoring via SNMP. It also supports SMTP, and will immediately send an e-mail on any error.

The T40+ is supplied with two power supplies to provide redundancy for mission critical operations and to avoid power interruption to the library. Both power supplies share the load under normal operating conditions. However, if one of the power supplies fails, the other will take the full load.

The Tandberg Data StorageLibrary family provides outstanding value for IT managers who need to perform large, unattended backups, and who require flexibility, reliability and a future-proof solution.



Key Benefits

- Capacity on Demand**
Start with 24 slots, expand to 151 slots, increasing capacity up to 453TB*
- Performance on Demand**
Add drives or upgrade to the next generation LTO technology to increase performance and meet demanding backup windows
- Ease of Management**
Browser-based remote management interface allows users to remotely monitor, control, configure and diagnose via the Internet
- Minimize Downtime**
The Redundant Power Supply (RPS) detects power failures and assures system availability
- WORM and Encryption**
WORM (write once read many) and Encryption for enhanced data protection and regulatory compliance

* Assumes a 2:1 compression ratio



The Tandberg Data StorageLibrary T40+ combines high capacity and performance in a scalable 4U form factor.

TANDBERG DATA
Securing your Information

Specifications

	StorageLibrary T40+	StorageLibrary T80+	StorageLibrary T120+	StorageLibrary T160+
Slots	24 or 40 slots	77 slots	114 slots	151 slots
Drive Technology	LTO-4 / LTO-5	LTO-4 / LTO-5	LTO-4 / LTO-5	LTO-4 / LTO-5
Number of Drives (Half height)	1-4	1-8	1-12	1-16
Number of Drives (Full height)	1-2	1-4	1-6	1-8
Number of Cartridges	24 or 40	77	114	
LTO-4 Capacity	19.2TB / 38.4TB (24 slots) 32TB / 64TB (40 slots)	61.6TB / 123.2TB	91.2TB / 182.4TB	120.8TB / 241.6TB
LTO-5 Capacity	36TB / 72TB (24 slots) 60TB / 120TB (40 slots)	115.5TB / 131TB	171TB / 342TB	226.5TB / 453TB
LTO-4 HH Performance/drive (SCSI, SAS)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)
LTO-4 HH Performance/drive (FC)	288GB/hr / 576GB/hr (80MB/sec / 160MB/sec)	288GB/hr / 576GB/hr (80MB/sec / 160MB/sec)	288GB/hr / 576GB/hr (80MB/sec / 160MB/sec)	288GB/hr / 576GB/hr (80MB/sec / 160MB/sec)
LTO-4 FH Performance/drive (SCSI, FC)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)	432GB/hr / 864GB/hr (120MB/sec / 240MB/sec)
LTO-5 HH Performance/drive (FC, SAS)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)
LTO-5 FH Performance/drive (FC)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)	0.5TB/hr / 1.0TB/hr (140MB/sec / 280MB/sec)
Interface	Ultra SCSI LVD, Native FC, SAS	Ultra SCSI LVD, Native FC, SAS	Ultra SCSI LVD, Native FC, SAS	Ultra SCSI LVD, Native FC, SAS
Remote Management (Web)	Standard	Standard	Standard	Standard
Barcode Scanner	Standard	Standard	Standard	Standard
Number of Removable Magazines	4	8	12	16
Temperature (Operating)	10C to 40C (50F to 104F)	10C to 40C (50F to 104F)	10C to 40C (50F to 104F)	10C to 40C (50F to 104F)
Temperature (Non-operating)	-30C to 60C (-22F to 140F)	-30C to 60C (-22F to 140F)	-30C to 60C (-22F to 140F)	-30C to 60C (-22F to 140F)
Relative Humidity, Non-Condensing (Operating / Non-operating)	20 to 80% / 10 to 90%	20 to 80% / 10 to 90%	20 to 80% / 10 to 90%	20 to 80% / 10 to 90%
Rackmount Option	Standard	Standard	Standard	Standard
Redundant Power Supply	Standard	Standard	Standard	Standard
Power Consumption	100-240VAC, 50-60Hz, 70W avg.	100-240VAC, 50-60Hz, 130W avg.	100-240VAC, 50-60Hz, 190W avg.	100-240VAC, 50-60Hz, 250W avg.
MTBF	250 000 hours	250 000 hours	250 000 hours	250 000 hours
Software Compatibility	The StorageLibrary T40+ is compatible with all major backup applications and operating systems			
Agency Certification	CE, FCC, TUV/GS, ICES VCCI, BSMI, CISPR 22, C-tick, C-UL, CB, GOST and EN 55022 Class A			
* Native / Compressed. Assumes a 2:1 compression ratio.				
Form Factor	4U	8U	12U	16U
Height	17.75cm (7 in)	35.5cm (14 in)	53.25cm (21 in)	71.0cm (28 in)
Width	44.66cm (17.6 in)	44.66cm (17.6 in)	44.66cm (17.6 in)	44.66cm (17.6 in)
Depth	73.6cm (29 in)	73.66cm (29 in)	73.66cm (29 in)	73.66cm (29.0 in)
Weight	37.7kg (82.9 lbs)	75.4kg (165.9 lbs)	113.1kg (248.8 lbs)	150.8kg (331.7 lbs)

About Tandberg Data

Tandberg Data is a leading global supplier of data protection solutions. Tandberg Data offers a wide selection of secondary storage solutions, ranging from disk-based solutions, such as the RDX® QuikStor™ and the Tandberg Data DPS Series, to automated tape solutions like the StorageLoader and StorageLibrary Series. Tandberg Data also offers tape drives, based on the DAT, LTO™, SLR™ and VXA® tape technology platforms, and media. Tandberg Data solutions are supported by robust, easy-to-use software. All solutions are supported through a worldwide service and support network, recognised globally for its outstanding levels of service. Tandberg Data solutions are designed to meet the growing storage requirements of small and medium-sized organisations with scalability, reliability, and backward compatibility features that ensure cost-effective operation and long-term investment protection.

DS-T40_EMEA_2010A

Tandberg Data GmbH
Feldstrasse 81
44141 Dortmund
Germany
Tel: +49 (0) 231 5436 - 0
Fax: +49 (0) 231 5436 - 111

Tandberg Data GmbH
Bloxham Mill Business Centre
Barford Road, Bloxham
Banbury, England, OX15 4FF
Tel: +44 845 070 6916
Fax: +44 1295 722 109

Tandberg Data S.A.S.
Multi Management Service
55 rue de l'Université
75007 Paris,
France
Téléphone: 00 800 826 323 74

Tandberg Data Corporation
10225 Westmoor Dr., Ste. 125
Westminster, CO 80021
USA
Tel: 303.442.4333
Fax: 303.417.7170

Tandberg Data (Asia) Pte. Ltd
7 Tai Seng Drive
#02-00
Singapore 535218
Tel: +65 6593 4700
Fax: +65 6281 7358

Specifications subject to change without notice. Tandberg Data StorageLoader, StorageLibrary, SecureService, DPS Series, RDX QuikStor and SLR are trademarks of Tandberg Data. RDX is a registered trademark of ProStor Systems. LTO is a trademark of HP, IBM and Quantum. All other trademarks are the property of their respective owners.
©2010 TANDBERG DATA. All rights reserved.

salesemea@tandbergdata.com 00 800 8263 2374 (00 800 TANDBERG)

www.tandbergdata.com/emea