

Product Line Card

HITACHI VIRTUAL STORAGE PLATFORM FAMILY MATRIX

	Hitachi Virtual Storage Platform G200	Hitachi Virtual Storage Platform G400	Hitachi Virtual Storage Platform G600	Hitachi Virtual Storage Platform G800 ¹	Hitachi Virtual Storage Platform G1000
Capacity Specifications					
Maximum (Max.) Number of Hard Drives, Including Spares	264 SFF 264 LFF	480 SFF 480 LFF	720 SFF 720 LFF	1,440 SFF 1,440 LFF	2,304 SFF 1,152 LFF
Max. Number of Flash Drives, Including Spares	264 SSD 264 FMD	480 SSD 480 FMD	720 SSD 720 FMD	1,440 SSD 1,440 FMD	384 SSD 576 FMD
Raw Capacity	1,008TB (4TB 3.5") 302TB (1.2TB 2.5") 614TB (3.2TB FMD) 77TB (400GB 2.5" SSD)	1,920TB (4TB 3.5") 576TB (1.2TB 2.5") 922TB (3.2TB FMD) 230TB (400GB 2.5" SSD)	2,880TB (4TB 3.5") 864TB (1.2TB 2.5") 922TB (3.2TB FMD) 230TB (400GB 2.5" SSD)	5,760TB (4TB 3.5") 1,728TB (1.2TB 2.5") 2,026TB (3.2TB FMD) 461TB (400GB SSD)	4,511TB (4TB 3.5") 2,656TB (1.2TB 2.5") 2,026TB (3.2TB FMD) 302TB (800GB SSD)
Flash Drive Options	3.2TB FMD 1.6TB FMD 400GB (2.5" MLC) 200GB (2.5" MLC)	3.2TB FMD 1.6TB FMD 400GB (2.5" MLC) 200GB (2.5" MLC)	3.2TB FMD 1.6TB FMD 400GB (2.5" MLC) 200GB (2.5" MLC)	3.2TB FMD 1.6TB FMD 400GB (2.5" MLC) 200GB (2.5" MLC)	3.2TB FMD 1.6TB FMD 800GB (2.5" MLC) 400GB (2.5" MLC)
SAS HDD Technology Options	4TB (3.5" 7.2K) 1.2TB (2.5" 10K) 600GB (2.5" 10K) 300GB (2.5" 15K)	4TB (3.5" 7.2K) 1.2TB (2.5" 10K) 600GB (2.5" 10K) 300GB (2.5" 15K)	4TB (3.5" 7.2K) 1.2TB (2.5" 10K) 600GB (2.5" 10K) 300GB (2.5" 15K)	4TB (3.5" 7.2K) 1.2TB (2.5" 10K) 600GB (2.5" 10K) 300GB (2.5" 15K)	4TB (3.5" 7.2K) 1.2TB (2.5" 10K) 900GB (2.5" 10K) 600GB (2.5" 15K) 600GB (2.5" 10K) 300GB (2.5" 15K)
Max. LFF (3.5") Disk Expansion Trays	7 (2U: 12 LFF) 4 (4U: 60 LFF/SFF)	16 (2U: 12 LFF) 8 (4U: 60 LFF/SFF)	24 (2U: 12 LFF) 12 (4U: 60 LFF/SFF)	48 (2U: 12 LFF) 24 (4U: 60 LFF/SFF)	12 (16U: 96 LFF)

	Hitachi Virtual Storage Platform G200	Hitachi Virtual Storage Platform G400	Hitachi Virtual Storage Platform G600	Hitachi Virtual Storage Platform G800	Hitachi Virtual Storage Platform G1000
Capacity Specifications					
Max. SFF (2.5") Disk Expansion Trays	7 (2U: 24 SFF)	16 (2U: 24 SFF)	24 (2U: 24 SFF)	48 (2U: 24 SFF)	12 (16U: 192 SFF)
Max. Hitachi Accelerated Flash Expansion Trays	7 (2U: 12 FMD)	16 (2U: 12 FMD)	24 (2U: 12 FMD)	48 (2U: 12 FMD)	16 (4x 2U: 48 FMD)
Block Module Specifications					
Number of Controllers	2	2	2	2	16
Height Width Depth²	2U, 3.4" (86mm) 19" (446mm) 30" (760mm)	4U, 6.9" (175mm) 19" (446mm) 34" (865mm)	4U, 6.9" (175mm) 19" (446mm) 34" (865mm)	4U, 6.9" (175mm) 19" (446mm) 34.1" (866mm)	10U, 17.5" (445mm) 19" (480mm) 48.6" (1235mm)
Weight With Disks Installed	24 SFF disks: 126 lbs. (57kg) 12 LFF disks: 134.5 lbs. (61kg)	187.4 lbs. (85kg)	187.4 lbs. (85kg)	187.4 lbs. (85kg)	312 lbs. (142kg)
Internal Drive Slots	12 LFF or 24 SFF	0	0	0	0
Host Interface Types	FC: 8Gb/sec, 16Gb/sec iSCSI: 10Gb/sec	FC: 8Gb/sec, 16Gb/sec iSCSI: 10Gb/sec	FC: 8Gb/sec, 16Gb/sec iSCSI: 10Gb/sec	FC: 8Gb/sec, 16Gb/sec iSCSI: 10Gb/sec	FC: 8Gb/sec, 16 Gb/sec IBM® FICON®: 8Gb/sec FCoE: 10Gb/sec
Host Port Counts	16 FC 8Gb/sec 8 FC 16Gb/sec 8 iSCSI 10Gb/sec	40 FC 8Gb/sec 20 FC 16Gb/sec 20 iSCSI 10Gb/sec	40 FC 8Gb/sec 20 FC 16Gb/sec 20 iSCSI 10Gb/sec	64 FC 8Gb/sec 32 FC 16Gb/sec 32 iSCSI 10Gb/sec	192 FC 8 Gb/sec 96 FC 16 Gb/sec 176 FICON 176 FCoE
Fibre Bandwidth to Host	12,800MB/sec	32,000MB/sec	32,000MB/sec	51,200MB/sec	256,000 MB/sec
Back-End Disk Interface	12Gb/sec SAS	12Gb/sec SAS	12Gb/sec SAS	12Gb/sec SAS	6Gb/sec SAS



	Hitachi Virtual Storage Platform G200	Hitachi Virtual Storage Platform G400	Hitachi Virtual Storage Platform G600	Hitachi Virtual Storage Platform G800	Hitachi Virtual Storage Platform G1000
Block Module Specifications					
Bandwidth to Drives	12,000MB/sec; 12Gb/sec SAS links, 4 per system	24,000MB/sec; 12Gb/sec SAS links, 8 per system	24,000MB/sec; 12Gb/sec SAS links, 8 per system	48,000MB/sec; 12Gb/sec SAS links, 16 per system	128,000MB/sec; 8 back-end directors; 6Gb/sec SAS links, 128 total
Maximum Cache	64GB	128GB	256GB	512GB	2TB
File Module Specifications³					
Recommended File Modules⁴	4040	4060	4060	4080	4100
Nodes per Cluster	1 - 2	1 - 4	1 - 4	1 - 4	1 - 8
Random I/O (Mixed loads)⁵	130,000	147,957	147,957	209,519	293,128
Height Width Depth	3U, 5.1" (130mm) 17.2" (437mm) 27" (685mm)	3U, 5.1" (130mm) 17.2" (437mm) 27" (685mm)	3U, 5.1" (130mm) 17.2" (437mm) 27" (685mm)	3U, 5.1" (130mm) 17.2" (437mm) 27" (685mm)	3U, 5.1" (130mm) 17.2" (437mm) 27" (685mm)
Weight	55 lbs. (25kg)	55 lbs. (25kg)	55 lbs. (25kg)	55 lbs. (25kg)	55 lbs. (25kg)
Main Board Memory	46GB (4GB NVRAM)	46GB (4GB NVRAM)	108GB (8GB NVRAM)	108GB (8GB NVRAM)	108GB (8GB NVRAM)
Number of VLANs	256	256	256	256	256
Protocols	NFS, SMB, FTP, HTTP, SSL, SNMP	NFS, SMB, FTP, HTTP, SSL, SNMP	NFS, SMB, FTP, HTTP, SSL, SNMP	NFS, SMB, FTP, HTTP, SSL, SNMP	NFS, SMB, FTP, HTTP, SSL, SNMP
1Gb/sec Client Ports	0	0	0	0	0
10Gb/sec Client Ports	4	4	4	4	4



	Hitachi Virtual Storage Platform G200	Hitachi Virtual Storage Platform G400	Hitachi Virtual Storage Platform G600	Hitachi Virtual Storage Platform G800	Hitachi Virtual Storage Platform G1000
Software Specifications					
RAID Supported	RAID-0, RAID-1, RAID-1+0, RAID-5, RAID-6	RAID-0, RAID-1, RAID-1+0, RAID-5, RAID-6	RAID-0, RAID-1, RAID-1+0, RAID-5, RAID-6	RAID-0, RAID-1, RAID-1+0, RAID-5, RAID-6	RAID-0, RAID-1, RAID-1+0, RAID-5, RAID-6
Max. Number of RAID Groups	84	240	240	480	575
Data-at-Rest Encryption	Yes	Yes	Yes	Yes	Yes
Max. LUN Size⁶	60TB	60TB	60TB	60TB	60TB
Max. Number of LUNs	2,048	4,096	4,096	16,384	65,280
Max. Number of File Systems (single/cluster)	128/125	128/125	128/125	128/125	128/125
Max. Number of Enterprise Virtual Servers (EVS)	64	64	64	64	64
Max. File System Size	256TB	256TB	256TB	256TB	256TB
Max. Number of Entries per Directory	16M	16M	16M	16M	16M
Max. Number of Snapshots	1,024 per file system; 1,024 per LUN; 100,000 per system	1,024 per file system; 1,024 per LUN; 100,000 per system	1,024 per file system; 1,024 per LUN; 100,000 per system	1,024 per file system; 1,024 per LUN; 100,000 per system	1,024 per file system; 1,024 per LUN; 100,000 per system
Max. Number of Virtual Volumes	10,000	10,000	10,000	10,000	10,000
Max. Number of User or Group Quotas	100,000	100,000	100,000	100,000	100,000
Max. Number of Hosts per Fibre Channel Port	255	255	255	255	255



	Hitachi Virtual Storage Platform G200	Hitachi Virtual Storage Platform G400	Hitachi Virtual Storage Platform G600	Hitachi Virtual Storage Platform G800	Hitachi Virtual Storage Platform G1000
Software Specifications					
Max. Number of IP Addresses per Cluster	256	256	256	256	256
Max. Number of IP Addresses per EVS	32	32	32	32	32
Number of Global Symlinks	10,000	10,000	10,000	10,000	10,000
Max. Number of CNS Links	500	500	500	500	500
Max. Number of SMB Shares	10,000	10,000	10,000	10,000	10,000
Max. Number NFS Exports	10,000	10,000	10,000	10,000	10,000
Max. Number of Concurrent NFS and/or SMB Clients	42,000	42,000	60,000	60,000	60,000
Max. Number of Concurrent FTP Clients	100	100	100	100	100
Max. Number of Concurrent Open Files: SMB	126,000	126,000	253,000	253,000	253,000
Max. Usable Capacity per Cluster	8PB	16PB	32PB	32PB	32PB

Notes:

- (1) Model available after initial release. Ask your HDS representative or partner for more information.
- (2) Dimensions provided are for the block controller chassis. Each model also requires a 1U service processor in addition to the controller chassis.
- (3) File module specs are per node unless otherwise indicated.
- (4) All file modules are supported with every VSP model.
- (5) Dual node values estimated based upon internal data.
- (6) Specifications represent the maximum addressable limit in a planned future release. Contact your HDS representative or HDS reseller partner for details regarding availability.

SFF = small form factor, LFF = large form factor, SAS = serial attached SCSI, HDD = hard disk drive, SSD = solid state disk, SATA = serial advanced technology attachment, MLC = multilevel cell, FMD = flash module drive, FC = Fibre Channel, FCoE = Fibre Channel over Ethernet, CNS = cluster namespace, NVRAM = nonvolatile random access memory, VLAN = virtual local area network, EVS = Enterprise Virtual Servers, SMB = Server Message Block, NFS = Network File System



@Hitachi Data Systems



Corporate Headquarters

2845 Lafayette Street
Santa Clara, CA 96050-2639 USA
www.HDS.com community.HDS.com

Regional Contact Information

Americas: +1 408 970 1000 or info@hds.com
Europe, Middle East and Africa: +44 (0) 1753 618000 or info.emea@hds.com
Asia Pacific: +852 3189 7900 or hds.marketing.apac@hds.com